

# SB-3 PASSIVE-RADIATOR SUBWOOFER

Passive-radiator technology & unique design are combined into a high-dynamic range & low distortion subwoofer system that matches the styling of our full-range models. It also hides easily in classrooms and other small spaces.

## DRIVER COMPLIMENT

One 8" active subwoofer driver and two 8" passive radiators

## FREQUENCY RESPONSE

42Hz to 875Hz +/- 3dB (with no EQ)

## POWER HANDLING

80W continuous RMS, 160W program (both coils driven)

## SENSITIVITY

(1W @ 1 Meter) = 86 dB

## MAX SPL

105 dB at 80W

## NOMINAL IMPEDANCE

2x 8Ω

Recommended crossover at 100Hz to 150Hz

## MOUNTING

200mm VESA mounting holes on reverse (Use standard VESA mount rated at least 40 lbs.)

## DIMENSIONS

36" x 10.5" x 9.5"

## WEIGHT

Approximately 40 lbs.

## A SUBWOOFER FOR CHURCHES, LARGE CLASSROOMS AND SMALL AUDITORIUMS

Use these subwoofers in multiples to handle larger spaces and live performances.

## IDEAL FOR MUSIC PLAYBACK

With the addition of these subwoofers, the GO Audio SA-12 and SA-6 become a full-range solution. Speech, music, soundtracks, & sound effects will all be faithfully reproduced.

## CLEAN STYLING

Each SB-3 is made up of three 8" transducers, with a total width of 10.5" and 3' tall. At only 9.5" deep it can be mounted conveniently to any wall with a standard 200mm (40 lb. rated) VESA mount.

## RUGGED FINISH

Each SB-3 is coated with an ultra-hard sprayed-on finish that resists wear. Available in white or black.

